

The tried & tested FETZEL laminators:

UNIVERSAL PRECISE ROBUST

Today's generation of tried & tested laminators for laminating various substrates with dry films of all kinds.

The decisive advantages:

- separately heatable, easily replaced rollers with silicone-rubber coating;
- temperature of each roller separately adjustable; with contact-free measurement;
- continuous adjustment of roller gap and roller application force;
- 2 film coils with 3" mountings
- 2 rewinders for protective film
- available in tabletop or standalone machine versions
- custom-made versions according to your requirements



in the picture: SDL 50.3 with the options: undertable (free-standing machine), emergency stop cord switch, powered feed table, digital speed display

Technical specifications	SDL Standard	UVL Universal
Working width	500 mm	600 mm
Rollers ϕ 84	heated up to 200°C (depending on type)	
Temperature control	separate / roller - contactless	
Roller gap	infinitely adjustable 0-10mm	
Application force	infinitely adjustable up to 2kN	
Drive	forward / reverse	
Speed	infinitely adjustable 0-3m/min	
Outfeed rollers	spring-mounted / run somewhat faster	
Basic dimensions (L x B)	1150 x 550 mm	1250 x 550 mm
Weight	130 – 170 kg	140-190 kg
Connection values	4.5 kW – 400 V	5 kW – 400 V
Connections	electr.: 16A / pneumatic: 6 bar	

The big advantage:

Planning, fabrication and fitting from single source!

→ Contact us without any commitment!

Standard – Options:

- ◆ undertable with cord switch
- ◆ application pressure amplification
- ◆ vapor extraction hood
- ◆ antistatic device
- ◆ preheating
- ◆ dust extraction
- ◆ digital displays for temperature / application pressure

Customizations:

- ◆ roller coatings: Viton, steel, stainless steel, Teflon, glue-repellent surface
- ◆ various infeed and outfeed tables (extended, powered,...)
- ◆ product unwinder